

DIAFLOW FILTER CATALOGUE



DIAFLOW PUMPS & FILTERS PVT. LTD.

Plot No. 209/210, Pash II New G.I.D.C. Gundlav, Valsad.

diaflowvalves@rediff.com

Manufacturer of Filters, Butterfly Valves, Basket Strainers, Damper Valves, Gauge, Savers, Priming Chambers, Tower Packing.



PFU 200 GF	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber	16
Dia. Of Plates	204 mm
M.O.C. - Plates	P.P.
Max. Pressure	1.2 kg/mtr ²
Max. Operating Temp.	60 °C
Max. Capacity	6000 Ltr / hr
Pump Model	DMP 100 IMS



PFU 200 GF DUPLEX	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber	16 + 16
Dia. Of Plates	204 mm
M.O.C. - Plates	P.P.
Max. Pressure	1.2 kg/mtr ²
Max. Operating Temp.	60 °C
Max. Capacity	12000 Ltr / hr
Pump Model	DMP 200 IMS



CFU 200 GF	
M.O.C. – Chamber	Moulded GF PP
No. Of Cartridge In Chamber	5
Cartridge length	10"
M.O.C. - Cartridge	P.P.
Max. Pressure	1.2 kg/mtr ²
Max. Operating Temp.	60 °C
Max. Capacity	6000 Ltr / hr
Pump Model	DMP 100 IMS



CFU 200 GF DUPLEX	
M.O.C. – Chamber	Moulded GF PP
No. Of Cartridge In Chamber	5 + 5
Dia. Of Plates	10"
M.O.C. - Plates	P.P.
Max. Pressure	1.2 kg/mtr ²
Max. Operating Temp.	60 °C
Max. Capacity	12000 Ltr / hr
Pump Model	DMP 200 IMS



PFU 300 GF	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber Each	20
Dia. Of Plates	304 mm
M.O.C. - Plates	P.P.
Max. Pressure	1.48 kg/mtr ²
Max. Operating Temp.	60 °C
Max. Capacity	12000 Ltr / hr
Pump Model	DMP 200 IMS



PFU 300 GF DUPLEX	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates in chamber	20 + 20
Cartridge length	304 mm
M.O.C. - Cartridge	P.P.
Max. Pressure	1.48 kg/cm ²
Max. Operating Temp.	60 °C
Max. Capacity	24000 Ltr / hr
Pump Model	DMP 300 IMS



CFU 300 GF	
M.O.C. – Chamber	Moulded GF PP
No. Of Cartridge in chamber	12
Cartridge length	20"
M.O.C. - Cartridge	P.P.
Max. Pressure	1.6 kg/cm ²
Max. Operating Temp.	60 °C
Max. Capacity	10000 Ltr/hr
Pump Model	DMP 200 IMS



CFU 300 GF DUPLEX	
M.O.C. – Chamber	Moulded GF PP
No. Of Cartridge in chamber	12 + 12
Cartridge length	20"
M.O.C. - Cartridge	P.P.
Max. Pressure	1.6 kg/cm ²
Max. Operating Temp.	60 °C
Max. Capacity	20000 Ltr/hr
Pump Model	DMP 300 IMS

PFU 400 GF	
M.O.C. – Chamber	Moulded GFPP
No. Of Plate In Chamber	10
Dia. Of Plates	375 mm
M.O.C. – Plates	P.P.
Max. Operating Temp.	60 °C
Max. Capacity	20000 <i>Ltr/hr</i>
Pump Model	DMP 300 IMS



CFU 400 GF	
M.O.C. – Chamber	Moulded GFPP
No. Of Cartridge In Chamber	16
Cartridge length	30"
Max. Pressure	1.8 <i>kg/cm²</i>
Max. Operating Temp.	60 °C
Max. Capacity	20000 <i>Ltr/hr</i>
Pump Model	DMP 300 IMS



SFP 85	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber	20
Dia. Of Plates	85 mm
M.O.C. - Plates	P.P.
Max. Pressure	0.8 kg / cm ²
Max. Operating Temp.	60 °C
Max. Capacity	3000 Ltr / hr
Pump Model	DMP 50 IMS



SFP 145	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber	20
Dia. Of Plates	145 mm
M.O.C. - Plates	P.P.
Max. Pressure	0.8 kg / cm ²
Max. Operating Temp.	60 °C
Max. Capacity	4000 Ltr / hr
Pump Model	DMP 50 IMS



SFP 200	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber	20
Dia. Of Plates	200 mm
M.O.C. - Plates	P.P.
Max. Pressure	1.2 kg / cm ²
Max. Operating Temp.	60 °C
Max. Capacity	9000 Ltr / hr
Pump Model	DMP 100 IMS



SFP 300	
M.O.C. – Chamber	Moulded GF PP
No. Of Plates In Chamber	20
Dia. Of Plates	304 mm
M.O.C. - Plates	P.P.
Max. Pressure	1.7 kg / cm ²
Max. Operating Temp.	60 °C
Max. Capacity	15000 Ltr / hr
Pump Model	DMP 200 IMS

FILTER PLATES AVAILABLE IN DIFFERENT SIZES



SIZE - 85 mm



SIZE - 145 mm



SIZE - 200 mm



SIZE - 300 mm



SIZE - 400 mm



SIZE - 10 Inch



SIZE - 20 Inch



SIZE - 30 Inch